Material Safety Data Sheet



1. Product and company identification

Product name : Buna VSL VP PBR 4045 Supplier/Manufacturer : LANXESS Corporation

Product Safety & Regulatory Affairs

111 RIDC Park West Drive Pittsburgh, PA 15275-1112

USA

For information: US/Canada (800) LANXESS

International +1 412 809 1000

<u>In case of emergency</u>: Chemtrec (800) 424-9300

International (703) 527-3887

Lanxess Emergency Phone (800) 410-3063.

Synonym : SBR

Material Number : 56806125

Chemical family : Synthetic rubber

2. Hazards identification

Physical state : Solid. [rubber bales]

Odor : Faint odor.

Color : Brown.

Emergency overview : CAUTION!

NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED. MAY CAUSE MECHANICAL IRRITATION (ABRASION). TOXIC AND IRRITATING GASES/FUMES

MAY BE GIVEN OFF DURING BURNING OR THERMAL DECOMPOSITION.

CONTACT WITH HOT MATERIAL WILL CAUSE THERMAL BURNS.

TERMPERATURES ABOVE 392 F (200C), THE PRODUCT DECOMPOSES

EXOTHERMICALLY WITH POSSIBILITY OF IGNITION.

Medical conditions

aggravated by over-

exposure

: None known.

Potential acute health effects / Over-exposure signs/symptoms

Inhalation: Inhalation is unlikely due to the low vapor pressure. May cause mechanical irritation

(abrasion).

Ingestion: No known significant effects or critical hazards.

Skin: May cause mechanical irritation (abrasion). Contact with hot material will cause thermal

burns.

Eyes: May cause mechanical irritation (abrasion).

Potential chronic health effects

Chronic effects: No known significant effects or critical hazards.

Carcinogenicity : No carcinogenetic substances as defined by IARC, NTP and/or OSHA.

3. Composition/information on ingredients

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Name CAS number %

No hazardous ingredient

Other Ingredients:

The following potentially hazardous ingredient(s) are contained at levels below disclosure requirements and are provided for informational purposes only.

The concentrations reported below in units of parts per million (ppm) or parts per billion (ppb) are maximum values. Hexane CAS# 110-54-3 <70ppm

4. First aid measures

Eye contact: Check for and remove any contact lenses. In case of contact flush eyes with plenty of

luke warm water. Get medical attention if symptoms occur.

Skin contact: Wash with plenty of soap and water. Get medical attention if symptoms occur. Get

medical attention if thermal burns occur. Wash clothing before reuse. Clean shoes

thoroughly before reuse.

Inhalation : If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical

personnel. Get medical attention if symptoms occur.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Extinguishing media

Suitable : In case of fire, use water spray (fog), foam or dry chemical.

Not suitable : Carbon dioxide (CO₂).

Special exposure hazards : Toxic and irritating gases/fumes may be given off during burning or thermal

decomposition.

Hazardous thermal : Decomposition products may include the following materials: carbon dioxide

carbon dioxide carbon monoxide

Special protective : Fire-fighters should wear appropriate protective equipment and self-contained breathing

: The product decomposes exothermically with possibility of ignition.

equipment for fire-fighters apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on fire hazards

6. Accidental release measures

Personal precautions : N

: No action shall be taken involving any personal risk or without suitable training.

Spill and Leak Procedures. : Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. If molten, allow material to cool and put into an appropriate container for

disposal.

Buna VSL VP PBR 4045 56806125 Version 2 **2/6**

7. Handling and storage

Handling

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Storage temperature:

: Do not store above the following temperature: 35°C

8. Exposure controls/personal protection

Hexane (110-54-3)

U.S. ACGIH Threshold Limit Values

Time Weighted Average (TWA): 50 ppm

OSHA PEL

Time Weighted Average (TWA): 1800 ppm, 500 ppm

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: Engineering controls should be sufficient to ensure airborne levels do not approach or exceed the exposure limit value for residuals. Thermal processing operations should be ventilated to control gases and fumes given off during processing.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Although no exposure limit has been established for this product, the OSHA PEL for Particulates Not Otherwise Regulated (PNOR) of 15 mg/m3 - total dust, 5 mg/m3 - respirable fraction is recommended. In addition, the ACGIH recommends 3 mg/m3 - respirable particles and 10 mg/m3 - inhalable particles for Particles (insoluble or poorly soluble) Not Otherwise Specified (PNOS).

Hands

: When handling hot material, wear heat-resistant protective gloves that are able to withstand the temperature of molten product.

Eyes

: safety glasses with side-shields

Skin

: Wear cloth work clothing including long pants and long-sleeved shirts. Suitable

protective footwear.

9. Physical and chemical properties

Physical state : Solid. [rubber bales]

Color : Brown.

Odor : Faint odor.

Density : 0.95 g/cm³

Solubility: Insoluble in the following materials: cold water.

Buna VSL VP PBR 4045 56806125 Version 2 **3/6**

10. Stability and reactivity

Chemical stability: The product is stable.

Conditions to avoid : Keep away from heat and direct sunlight.

Materials to avoid

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

: No specific data.

Possibility of hazardous

reactions

: Exposure to high temperatures causes exothermic reaction or decomposition.

For a constant black to account many accounts a conflict many larger than and

11. Toxicological information

No information available.

Product/ingredient name CAS # IARC NTP OSHA

Not available.

12. Ecological information

Aquatic ecotoxicity

No information available.

13. Disposal considerations

Waste disposal: Waste disposal should be in accordance with existing federal, state, provincial and/or

local environmental controls. The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This

material and its container must be disposed of in a safe way.

Empty Container Precautions.

: Recondition or dispose of empty container in accordance with governmental regulations.

RCRA classification : If discarded in its purchased form, this product would not be a hazardous waste either

by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. (40 CFR

261.20-24)

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	 Additional information
DOT Classification	-	-	-	-	Not regulated.
IMDG Class	-	-	-	-	Not regulated.
IATA-DGR Class	-	-	-	-	Not regulated.

PG*: Packing group

RQ : 0 lbs

Regulatory information **15**.

HAZCOM Standard Status

: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.

SARA Section 311/312 **Hazard Categories**

: None

: None

Ingredient name CAS number **Concentration**

(%)

SARA Title III Section 302 Extremely Hazardous

Substances

Ingredient name

CAS number

Concentration

(%)

SARA Title III Section 313

: None

Toxic Chemicals

Ingredient name

CAS number

RQ

US EPA CERCLA Hazardous : None

Substances (40 CFR 403)

State regulations

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections on the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropraite agency in your state.

Ingredient name **CAS** number **State Code** Concentration (%) Styrene-Butadiene Copolymer 9003-55-8 60 - 100

Massachusetts Substances: MA - S

Massachusetts Extraordinary Hazardous Substances: MA - Extra HS

New Jersey Hazardous Substances: NJ - HS

Pennsylvania RTK Hazardous Substances: PA - RTK HS Pennsylvania Special Hazardous Substances: PA - Special HS


California Prop. 65

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer. WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	CAS#	Concentration (%)	<u>Cancer</u>	Reproductive
1,3-Butadiene	106-99-0	< 0.1	Yes	Yes
U.S. Toxic Substances Control Act	: Listed on th	e TSCA Inventory.		

16. Other information

Hazardous Material Information System




0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

*=Chronic

The customer is responsible for determining the PPE code for this material.

16. Other information

National Fire Protection Association (U.S.A.)



0= Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

LANXESS' method of hazard communication is comprised of Product Labels and Material Safety Data Sheets. HMIS and NFPA ratings are provided by LANXESS as a customer service.

Contact person : Product Safety and Regulatory Affairs

Date of issue: 08-31-2011Date of previous issue: 08-31-2011

Version : 2

Indicates information that has changed from previously issued version.

Notice to reader

This information is furnished without warranty, express or implied. This information is believed to be accurate to the best knowledge of LANXESS Corporation. The information in this MSDS relates only to the specific material designated herein. LANXESS Corporation. assumes no legal responsibility for use of or reliance upom the information in this MSDS.

Buna VSL VP PBR 4045 56806125 Version 2 **6/6**